

maeli

 $\textbf{MAFELL AG} \cdot \text{Postfach } 11\,80 \cdot \text{D-}78720 \text{ Oberndorf a. N.} \cdot \text{Telefon } +49\,74\,23/8\,12-0 \cdot \text{Fax } 8\,12-218 \cdot \text{E-Mail mafell.@mafell.de} \cdot \textbf{www.mafell.de}$ 

Portable Bandsaw Z 5 Ec		Ref. No. 925301	
Technical data	Z 5 Ec		
Cutting depth	305 mm		
1 band side tiltable	0 - 30°		
Nominal speed no load	650 - 1550 1/min		
Nominal input	2250 W		
Weight	13,7 kg		
Universal-motor	230 V / 50 Hz		
Cutting speed	6,9 - 16,6 m/s		
Delivery scope includes:		Ref. No.	
1 Saw band 8 mm (5/16 in.) 4 teeth per inch, with front and rear cutting teeth			
1 Saw band 8 mm (5/16 in.) 4 teeth per inch			
1 Saw band 6 mm (1/4 in.) wide 4 teeth per inch			
1 Handle for two-man operation		203824	
1 Parallel guide fence		039386	
1 Mains cable 10 m (32.8 ft)		087863	
Accessories / Tools		Ref. No.	
Guide rail length 3 m (9.8 ft), (2 pieces with connecting piece)		037037	
Guide rail, length 3 m (9.8 ft) (one piece)		200672	
Guide rail extension 2600 length 1,5 m (4.9 ft)		036553	
Adapters (pair) for parallel guide fence		037195	
Trolley		202110	
Band saw blades, 10 pcs., 6 mm (1/4 in.) wide, 6 teeth per inch, for curved cuts		092333	
Band saw blades, 10 pcs., 6 mm (1/4 in.) wide,			
6 mm (1/4 in.) wide, 4 teeth per inch, for curved cuts		092335	
Band saw blades, 10 pcs., 8 mm (			
4 teeth per inch, for mainly straight cuts		092336	
Band saw blades, 10 pcs., 8 mm (5/16 in.) wide,			
4 teeth per inch, with front and rear cutting teeth for easy reversing		092337	

Ihr MAFELL-Fachhändler – unser Vertriebspartner:



# Portable Bandsaw Z 5 Ec



Subject to design modifications and changes to delivery some in the interests of monays. Bef. No. 902073 : 06/12 : Prin


## New generation of portable bandsaw: Z 5 Ec.

## high on performance, low on weight.

The efficient blower ensures a clear view of the mark.

Thanks to high torque, solid wood and cutting depth up to 305 mm respectively is no problem for the and Z 5 Ec.

MAFELL benefit: its versatility makes the Z 5 Ec ideal machine - especially when renovating old buildings.




Great flexibility and a broad field of application are facilitated by extensive optional accessories, including a trolley, pair of adapters, guide rails with extension, and a variety of blades.






innovative successor to the legendary Z 3. **CUprex** and magnesium die-cast components, its persuasive benefits include reduced weight, enhanced performance, higher torque and excellent handling. For thicker work, the otherwise identical Z 5 Ec offers an

The **precision** that typifies MAFELL portable bandsaws enables the Z 5 Ec to execute extremely clean and perfectly square cuts.



develops generous torque and delivers an output of 2250 Watt. The continuously variable speed range, from 650 to 1550 rpm, ensures compliance with individual requirements and applications.



### **Blower**

The cooling air of the high-performance motor is utilized to blow away dust from the mark. As a consequence, chips are kept well away from your head and you maintain a clear view of the mark at all times.

## Safety brake

The mechanical safety brake is engaged by the combined brake/off switch and, like the built-in voltage drop circuit, further enhances safety.

## Tilting blade guide

The unique tilting blade guide allows right-angle cuts to be made up to 90 mm deep without the opposite side of the blade touching the wood, e.g. when cutting lapped joints.

#### Blade

The back-toothed blade facilitates retraction from the cut, which is especially easy if the blade is locked by the mechanical brake.



#### **Changing blades**

With a spring-mounted and tensioned idler wheel, changing blades is an easy and quick procedure.



