



New ADJUSTABLE female fence

Optional. Suitable for jigs B & N



The new left/right adjustable female fence from 0 to 50°



Fence fitted on the female plate



Adjustable female fence and female plate fitted on a principal rafter



Principal rafter after the mortise machining. Look at the straight mortise (slanted compared to the beam).



A principal rafter and its purlin fitted together. The rafter is reclined and the purlin is straight.

Use of the fences

These new adjustable female fences can be used to realize **angle mortises on the principal rafters or on trusses** (straight mortises on the principal rafters or trusses).

Assembly and compatibility of the fences

These new adjustable fences can be used exclusively on:

- Female plates of the **jigs class B** (50 B, 80 B, 120 B, 160 B)
- Female plates of the **jigs class N** (50 N, 80 N, 120 N)

Angle of the fences

The angle of the fences can be adjusted from 0° to 50°, on the left and on the right.

This new optional accessory pushes the limits of the Arunda jigs, allowing users to produce a wider diversity of dovetail assemblies.

Item No., adjustable female fence (for) : (50B) Item No. 04.1050 - (50N) Item No. 04.1051 - (80B) Item No. 04.1080 - (80N) Item No. 04.1081 - (120B) Item No. 04.1120 - (120N) Item No. 04.1121 - (160B) Item No. 04.1160